# SUPERDOME DRUM



BENT MANUFACTURING COMPANY

## SUPERDOME DRUM

### and BASE

#### **FEATURES:**

- Double (one on each side) flag mount holes with pre-molded stops for all-purpose flagging situations.
- Enlarged arch carry handle allows gloved workers easy, comfortable and secure grip.
- Ribbed dome top for increased target value and superior structural strength.
- High gravity molded rubber base hugs the road as if it were "glued down."
- Recessed reflective band tiers, maximum width 6".
   Accommodates USA M.U.T.C.D. 2" maximum spacing specifications.
- Two pre-molded light mounts are designed for standard size bolt and cup washers.
- Rounded dome top discourages any dangerous debris or rocks to collect on top of drum.
- Tested and certified to meet the crashworthy requirements of NCHRP-350.



Low or high density polyethylene

### SPECIFICATIONS: Drum Materials





Color	Cad. orange				
Drum Weight	LDPE (12 lbs), HDPE (10 lbs)				
Drum Height	Base of drum to bottom of dome – 36"				
	(meets Fed. M.U.T.C.D. VI, Section 6F-5e.)				
	Base of drum to top of dome $-39$ " / Base of drum to top of handle $-41^{1/2}$ "				
Drum Diameter	18" minimum (meets Fed. M.U.T.C.D. Part VI, Section 6F-5e.)				
Reflectivity	H.I. / E.G. / D.G.				
Reflective Band Size	4" / 6"				
Light Brackets	2 each				
Flag Brackets	2 each				
OPTIONAL BASE					
Base Material	Molded rubber snap-on base	Drop over base (natural bio-degradable	Drop over base (blow-molded polyethylene	Sand filled snap-on (LDPE/ HDPE)	Sand bag snap-on base (LDPE/ HDPE)
		materials or molded rubber	plastic, sand fillable)		
Base Weight	25, 30, 40 lbs	28 lbs	3 <sup>1</sup> / <sub>2</sub> lbs (empty) to 40 lbs (filled)	4 to 40 lbs	21/2"
Base Height	2.8"	3.25"	3.5"	3.5"	3.5"
Base Diameter	24"	26"	26"	24"	24"
Base Color	Black	Natural/black	Black/ cad. orange	Cad. orange	Cad. orange

All specifications and descriptions are subject to change without notification.

Patent No. 5,722,788

#### Bent Manufacturing Company, Inc.

17311 Nichols Street

Huntington Beach, CA 92647-5721

(714) 842-0600 • FAX (714) 842-2959

(888) 842-0600 • FAX (888) 842-2368

E-Mail: BMC@bentmfg.com http://www.bentmfg.com

Distributed by: